



Pro Performance Full Synthetic SAE 50 Manual Transmission Fluid

Pro Performance Full Synthetic SAE 50 Manual Transmission Fluid is a synthetic manual transmission lubricant. It contains anti-wear additives as well as rust, oxidation and corrosion inhibitors that protect bearings and synchronizers, reduce component wear and promote longer transmission and lubricant life. It is suitable for use in applications calling for API MT-1 EP gear oil service classification and for use in transmissions and gear cases where API Service GL-1 through GL-4 is required.

Note: This product is NOT suitable for use in hypoid gear applications in differentials and final drives where API Service GL-5 is required.

This product is NOT approved for Eaton Roadranger and ArvinMeritor Extended Warranties. For those applications use **Lubriguard Full Synthetic HD Manual Transmission Fluid SAE 40**.

Benefits

- Reduced wear
- Long service life
- Outstanding low temperature performance
- Reduces drag for optimum fuel economy



RAINBO OIL COMPANY.
Delivering Performance Every Day

1-800-942-4425
www.rainbolubes.com



Pro Performance Full Synthetic SAE 50 Manual Transmission Fluid

Typical Characteristics

SAE Viscosity Grade		50
Viscosity	ASTM D 445	
@ 40°C, cSt		129.0
@100°C, cSt		18.0
Viscosity Index	ASTM D 2270	155
Pour Point, °F (°C)	ASTM D 97	-40 (-40)
Flash Point, °F (°C)	ASTM D 92	428 (220)
Gravity, API	ASTM D 287	34.6

Package	Product Code #
Bulk	148000
Tote	148098
Drum	148012
Keg	148018
Pail	148009



RAINBO OIL COMPANY.
Delivering Performance Every Day

1-800-942-4425
www.rainbolubes.com