



Pro Performance Full Synthetic GL-5 Gear Oils

Pro Performance Full Synthetic GL-5 Gear Oils are multi-purpose gear lubricants designed for API Service Classification “GL-5” and “MT-1”.

Pro Performance Full Synthetic GL-5 Gear Oils are compounded with highly refined synthetic base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust preventions, low pour point, and anti-foaming performance. These products are formulated for use in limited slip differentials.

Pro Performance Full Synthetic GL-5 Gear Oils may be used in applications calling for API GL-5, API MT-1, SAE J2360, and Mack GO-J (75W-140) and Mack GO-J Plus (75W-90).

Pro Performance Full Synthetic GL-5 Gear Oils are recommended for use in limited slip and conventional differentials of heavy duty trucks, cars, light trucks and sport utility vehicles. Always check owner’s manual for proper recommendation. Note: These products are not approved for Eaton Roadranger and ArvinMeritor Extended Warranties. For those applications use LubriGuard Heavy Duty Synthetic Gear Lubricants.

Benefits

- Reduced wear
- Long service life
- Exceptional low temperature performance
- Reduces drag for optimum fuel economy
- Full Limited Slip performance



RAINBO OIL
COMPANY®
Delivering Performance Every Day

1-800-942-4425

www.rainbolubes.com



PRO PERFORMANCE

Pro Performance Full Synthetic GL-5 Gear Oils

Typical Characteristics

SAE Viscosity Grade	75W-90	75W-140
Pour Point Deg F.	-46	-40
Flash Point, COC, °F	410	420
Viscosity		
@ 40°C, cSt	100	175
@100°C, cSt	15.4	26.2
Viscosity Index	163	186
Specific Gravity @ 60°F	0.865	0.864
Density (lbs/gal)	7.19	7.18
Rust Test, ASTM D665	Pass	Pass
Product Code #		
Bulk	158000	168000
Drum	158019	168019
Keg	158018	168018
Pail	158017	168017
12/1 Quart	158001	168001