

Pro Performance Universal Tractor Fluid

Pro Performance Universal Tractor Fluid is formulated from premium base stocks and state-of-the-art additive technology. It is designed for use in a variety of farm equipment, off-highway machinery, industrial ractors, final drives, power take-off units, wet brakes, power steering units and hydraulic systems.

Pro Performance Universal Tractor Fluid is made with special friction modifiers combined with extremely shear-stabile viscosity modifiers offer a supreme performance level. This new and improved fluid offers the convenience of using one tractor fluid in place of two or more fluids while maintaining optimum component performance and durability.

APPLICATIONS: Pro Performance Universal Tractor Fluid is suitable for use in all major OEM equipment including but not limited to Kubota, Oliver, Minneapolis-Moline, International Harvester, White Farm, John Deere, Deutz-Allis Chalmers, Ford-New Holland, J.I. Case and Massey Ferguson.

Pro Performance Universal Tractor Fluid is suitable for use where the following specifications are recommended:

- John Deere Quatrol, J20A, J20C, J21A, Hy-Gard J14B/C, Type 303
- International Harvestor Hy-Tran, B-6
- Massey Ferguson M-1110, M-1127B, M-1129A, M-1135, M-1141
- Allis Chalmers Power Fluid 821 XL
- J.I. Case TFD (JIC-143/146), Hi-Vis (JIC-185), JIC-144/145, MS-1204, MS1205/1206/1207, MS-1210 (TCH) and B-6
- Ford New Holland M2C86-A/B/C, M2C134-A/B/C/D, M2C41-B, M2C43, M2C53-A/B, M2C92-A
- Vickers I-2986-S
- Kubota Universal Transdraulic Fluid- UTD

FEATURES AND BENEFITS:

- Superior wear protection
- Excellent rust and corrosion protection
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature



1-800-942-4425 www.rainbolubes.com



Typical Characteristics	
Specific Gravity	0.86
Lbs. / gallon	7.2
Viscosity, cPs @ 100 ℃	9.6
Viscosity, cPs @ 40 ℃	54.4
Viscosity Index	119
Flash Point, C °	218
Pour Point, C°	-35



1-800-942-4425 www.rainbolubes.com