



PRO PERFORMANCE

Pro Performance Multi-Purpose ATF

DESCRIPTION: Pro Performance Multi-Purpose ATF is an automatic transmission fluid designed for electronically-controlled transmissions. This product is specifically designed for use in General Motors transmissions calling for DEXRON® -III, DEXRON -IIE and DEXRON -II fluids. It can also be used in Ford transmissions calling for MERCON® type ATF's. CITGO TRANSGARD Multi-Purpose ATF meets the performance requirements for Allison Transmission Division (C-4) and major hydraulic pump manufacturers' requirements for anti-wear hydraulic fluids.

QUALITIES: Superior cold temperature performance characteristics. Wide range of seal compatibility. Excellent wear protection. Superior frictional characteristics with excellent friction retention and smooth shifting. Fortified against rust and corrosion. Excellent oxidation resistance. Meets requirements for foam protection. Dyed red for easy identification.

APPLICATIONS: Pro Performance Multi-Purpose ATF is recommended for use in automatic transmissions manufactured by General Motors and Ford for model years 2006 and prior (except those calling for FORD Type "F" Fluid, MERCON SP, MERCON V, DEXRON -VI and CVT fluids). This product is suitable for use in foreign cars and trucks requiring the use of DEXRON -III, DEXRON -IIE, DEXRON -II fluids, and MERCON type ATF's. CITGO TRANSGARD Multi-Purpose ATF is suitable for use in powershift transmissions, torque converters, hydrostatic transmissions and applications such as in air compressors, hydraulic pumps, power steering boxes and other types of service where an ATF is recommended.

Pro Performance Multi-Purpose ATF is a truly multifunctional transmission fluid for passenger cars, trucks, construction and mining equipment, farm machinery and other mobile and industrial systems. Consult owner's manual for fluid specification.

TYPICAL PROPERTIES:

PRO PERFORMANCE MULTI-PURPOSE ATF

Material Code 633135001

Gravity, ASTM D4052, °API 32.9	
Pounds Per Gallon	7.15
Flash Point, COC, ASTM D92, °F (°C)	424 (218)
Pour Point, ASTM D97, °F (°C)	-54 (-48)
Viscosity, ASTM D445, cSt at 40°C	34.3
cSt at 100°C	6.95
ASTM D2983, cP at 20°C	1,020
cP at -40°C	15,100
Viscosity Index, ASTM D2270	169
Color	Red

All registered trademarks or trademarks are the property of their respective owners.



RAINBO OIL
COMPANY®
Delivering Performance Every Day

1-800-942-4425
www.rainbolubes.com