

Pro Performance Premium (LS) Gear Oil

- **DESCRIPTION:** Pro Performance Premium (LS) Gear Oil is a multipurpose, "limited slip" automotive gear lubricant. Selected additives impart extreme pressure properties which protect automotive gears operated under the most severe service conditions encountered in passenger cars, trucks, farm tractors, earthmoving, construction and other heavy-duty equipment. These additives impart the antiweld, antiscuff and antiwear properties which are necessary in heavy-duty applications. The friction modifier meets the requirements of "positive traction" or "limited slip" type differentials.
 - QUALITIES: Pro Performance Premium (LS) Gear Oil is blended to meet the multigrade viscosity requirements described in SAE Standard J306. This gear lubricant is formulated with high VI, refined base oils and thus does not require viscosity improver to meet multigrade viscometric properties. Because this lubricant does not contain VI improver, it will maintain its viscometric properties throughout its useful life and will not lose viscosity through shear.

Equipment manufacturers' recommendations should be followed when the gear lubricant is subject to high ambient temperatures. While some gearsets are designed for year-round operation using an SAE 80W-90, others may require SAE 85W-140 for high ambient temperature operations.

Pro Performance Premium (LS) Gear Oil is designated for the highest severity of gear service, API Service Classification GL-5. Pro Performance Premium (LS) Gear Oil is on Mack Truck's list of approved GO-H lubricants.

APPLICATIONS: Pro Performance Premium (LS) Gear Oil is recommended for use where "multipurpose" gear oil or one suitable for API Service GL-5 is required.

Pro Performance Premium (LS) is for use in differentials of passenger cars and light trucks. Premium (LS) is also for use in limited slip differentials known as Sure-grip[®], Posi-trac[®], Trac-lock[®], etc., for complete fill or for top-off.

Pro Performance Premium (LS) is also for service in transmissions, differentials, final drives and other gearcases of trucks, buses and farm tractors where extreme pressure, hypoid or multipurpose gear oils are specified by the equipment manufacturer, including differentials.



1-800-942-4425 www.rainbolubes.com



Pro Performance Premium (LS) Gear Oil

TYPICAL PROPERTIES:

PRO PERFORMANCE PREMIUM (LS) GEAR OIL

SAE Grade	80W-90
Material Code	631330001
SAE Grade Gravity, ASTM D4052, °API Specific Gravity Density, lb/gal at 60°F Flash Point, COC, ASTM D92, °F (°C) Viscosity, ASTM D445, cSt at 40°C cSt at 100°C ASTM D2161, SUS at 100°F SUS at 210°F ASTM D2983, cP at -26°C Viscosity Index, ASTM D2270 Pour Point, ASTM D97 ⁽¹⁾ , °F (°C) Channel Point, °F (°C), Max. Foam Test, ASTM D892	80W-90 27.4 0.89 7.4 430 (221) 142 14.2 721 76 125,000 97 -27 (-33) -31 (-35) Pass

Notes: (1) Method 3456 of Federal Test Method Standard No. 791

All registered trademarks or trademarks are the property of their respective owners.



1-800-942-4425 www.rainbolubes.com